


Diesel Powered Generating Sets C2500 D5A



Standard Genset Features

Cummins water cooled Diesel engine,
Oil and fuel filter fitted, water separator
Lube-oil drain valve fitted
Electric starter & Charge alternator 24 v D.C.
Electronic governor
Normal duty air filter
Single bearing alternator, class H/H
Standard voltage 400/230 volts 50 Hz
Exciter/Voltage reg - Torque Match as standard
PCC3201 with Bargraph as standard
Steel base frame with A/V mounting,
Engine, Alternator, Chassis & Control Box
Munsell Jade Green
Radiator
Packing under shrunk plastic film
Operation & Maintenance manual
Standard set of labels

Generator Set Performance

Voltage Regulation
Maintains voltage output to within $\pm 1.0\%$.
At any power factor between 0.8 and 1.0
At any variations from No load to Full load
At any variations from Cold to Hot.
At speed droop variations up to 4.5%.
Frequency Regulation
Isochronous under varying loads from no
load to 100% full load when electronic
governor is fitted
Random Frequency Variation
Will not exceed $\pm 0.25\%$ of its mean value for
constant loads – no load to full load.
Waveform
Total harmonic distortion open circuit voltage
waveform in the order of 1.8%. Three-phase
balanced load in the order of 5.0%.
Telephone Influence Factor (TIF)
TIF better than 50.
THF to BS 4999 Part 40 better than 2%.
Alternator Temperature Rise
Class H insulation.
Radio Interference
In compliance with BS 800 and VDE levels
G and N.

Generator Set Options

Fuel options
Fuel Tank

Exhaust Options
Exhaust Silencer - Industrial In-Line
Exhaust Bellows
Exhaust Silencer - Residential , In-Line
Installation Kit - Industrial Silencer
Installation Kit - Residential Silencer

Voltage Connections
240/416V, 230/400V, 220/380V,
127/220V, 115/200V, 110/190V

Miscellaneous Options
3 pole or 4 pole Circuit Breaker
Optional Set mounted starting batteries
Coolant Heater 240V
Battery Charger 240V, 5A or 10A
Automatic Transfer Switches
Packing - Export Box

Engine Specification

QSK60G8
60° Vee
16-cylinder diesel engine.
Type
Water cooled, four cycle, turbocharged
and low temperature aftercooled
Construction
Two valves per cylinder, forged steel
crankshaft and connecting rods, cast iron
block.
Starting
24 volt negative earth. Battery charging
alternator 35 amp on engine. Cranking
current 1800 amps at 0°C.
Fuel System
24 volt fail safe actuator. Spin-on paper
element fuel filters with fuel pump
injection system with integral electronic
governor. Dual flexible fuel lines and
connectors. Standard fuel water separator.
Filters
Air cleaner with dry element.
Spin-on full flow lube oil filter.
Cooling
40°C ambient temperature standard
Stone guard. Drain Tap

Alternator Specification

Type
Brushless single bearing, revolving field,
pole, drip proof, screen protected.
Class H Insulation, IP23 Protection
Fully interconnected damper winding.
AC exciter and rotating rectifier unit.
Epoxy coated stator winding.
Rotor and exciter impregnated with tropical
grade insulating oil and acid resisting
polyester resin. Dynamically balanced rotor
BS 5625 grade 2.5.
Sealed for life bearings.
Layer wound mechanically wedged rotor

Exciter
Triple dipped in moisture, oil and acid
resisting polyester varnish and coated with
anti-tracking varnish.

Output windings with 2/3 pitch for improved
harmonics and paralleling ability.
Close coupled engine/alternator for perfect
alignment.

Compliance Standards

To BS4999/5000 pt 99,
VDE 0530, UTE5100,
NEMA MG1-22, CEMA,
IEC 34, CSA A22.2,
AS1359, BSS 5514,
ISO 3046 and ISO 8528

Model name	kVA		kWe	
	Standby	Prime	Standby	Prime
C2500 D5A	2500	2250	2000	1800

Technical Data

Model	C2500 D5A	Speed	1500rpm
Set output	380-440 V 50 Hz	Alternator voltage regulation	±1.0%
Prime Rating	1800 kW/ 2250 kVA	Alternator insulation class	H
Standby Rating	2000 kW/ 2500 kVA	Fuel consumption (Prime)	NA
Engine Make	Cummins	Fuel consumption (Standby)	500l/hr
Engine Model	QSK60G8	Lubrication system oil capacity	195 Litres
Cylinders	Sixteen	Base fuel tank capacity – open set	NA
Engine build	60° Vee	Coolant capacity	621 Litres
Standard Governor/Class	Electronic	Exhaust temp – prime	485°C
Aspiration and cooling	Turbocharged and Low Temperature Aftercooled	Exhaust gas flow – prime	6315 l/s
Bore and stroke	159 mm x 190 mm	Exhaust gas back pressure max	51 mm Hg
Compression Ratio	14.5:1	Air flow – radiator*	31.0 m³/s
Cubic capacity	60.2 Litres	Air intake – engine (Prime)	2605 Litres/s
Starting/Min °C	10°C	Minimum air opening to room	10.0 m³
Battery capacity	254 A/hr	Minimum discharge opening	6.7 m³
Gross Engine output – Prime	NA	Pusher fan head (duct allowance)*	13 mm Wg
Gross Engine output – Standby	2145 kWm	Heat radiated by eng (Prime)	205 kWm

PRIME POWER

Prime Power is available continuously during the period of power outage in a variable load application. Variable load should not exceed a 70% average of the prime power rating during any 24 hour period. A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation.

STANDBY POWER

The Standby Power is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating. In installations served by unreliable utility sources (where outages last longer or occur more frequently), where operation is likely to exceed 200 hours per year, the prime power rating should be applied.


The Standby Power rating is only applicable for emergency and standby applications where the generator set serves as the back up to the normal utility source.

All ratings are based on the following reference conditions:

- Ambient temperature : 27°C

- Altitude above sea level : 150 metres

- Relative humidity : 60%



Dimensions and Weights

Open Version

Model	Engine	Length (mm)	Width (mm)	Height (mm)	Dry weight without tank (Kg)	Wet weight without tank (Kg)
C2500 D5A	QSK60G8	5842	2270	2800	17000	17720

Specifications may change without notice

Cummins Power Generation
 Asia Pacific
 10 Toh Guan Road #07-01
 TT International Tradepark
 Singapore 608838
 Tel: (+65) 6417 2388
 Fax: (+65) 6417 2399
 Email: mktg.sing@cummins.com
www.cumminspower.com

See your distributor for more information.

